

DEWALT®

OSHA COMPLIANT
1926.1153

DUST SOLUTIONS

Compliant Versions available by June 2017

ARE YOU COMPLIANT?

The Occupational Safety and Health Administration (OSHA) has issued a final rule to curb lung cancer, silicosis, chronic obstructive pulmonary disease and kidney disease in America's workers by limiting their exposure to respirable crystalline silica. This rule requires engineering controls to keep workers from breathing silica dust.



TOOLS

Operate and maintain tool in accordance with manufacturer's instructions to minimize dust emissions.

- Read operator's manual provided with tool and accessories.
- To minimize dust emissions use recommended shroud or cowling with dust extractor



Compliant Versions available by June 2017

ACCESSORIES AND SHROUDS

Use drill or grinder equipped with commercially available shroud or cowling with dust collection system.

- All DEWALT shrouds and dust collection systems are commercially available.



DUST EXTRACTORS

Dust collector must provide the air flow recommended by the tool manufacturer, or greater, and have a filter with 99% or greater efficiency. Dust collector must have a cyclonic pre-separator or filter-cleaning mechanism. Cleaning/Drilling holes requires a vacuum with a HEPA filter.

- Both DWV010 and DWV012 provide the necessary airflow for drilling and hammering applications.
- Both DWV010 and DWV012 ship with dual HEPA filters, which have an efficiency of 99.97% of all particles greater than or equal to 0.3 microns.
- Both DWV010 and DWV012 have a timed automatic filter-cleaning mechanism.

**PERFORM
PROTECT**

YOUR FIRST LINE OF DEFENSE.



The Occupational Safety and Health Administration (OSHA) has issued a final rule to curb lung cancer, silicosis, chronic obstructive pulmonary disease and kidney disease in America's workers by limiting their exposure to respirable crystalline silica. This rule requires engineering controls to keep workers from breathing silica dust.



DRILLING

SDS+ DRILLING

SDS MAX & SPLINE DRILLING

CHIPPING & DEMOLITION

TOOL ATTACHMENT | ADAPTOR EXTRACTOR

SDS PLUS

≤ 1-1/8"

CORDLESS OPTIONS



1-1/8"



D25301D
Dust Extractor Telescope
with Hose



DWH9130
AirLock™ Adaptor
Included on D25301D



DWH050K
Large Hammer Drilling Dust Extraction



DWV012
or
DWV010
Dust Extractor



DWH9000
AirLock™ Adaptor
Included on
DWV012 & DWV010



DWH050K
Large Hammer Drilling Dust Extraction



DWH053K
Large Hammer Chipping Dust Extraction



DWV012
or
DWV010
Dust Extractor



DWV010
Dust Extractor



DWH053K
Large Hammer Chipping Dust Extraction



DWH053K
Large Hammer Chipping Dust Extraction



DWH052K
Breaker Dust Extraction



GRINDING¹

5-6" TUCKPOINTING / CUTTING¹

5" SURFACING

TOOL ATTACHMENT | ADAPTOR EXTRACTOR



DWE46100
5-6" Cutting and Tuckpointing
Dust Shroud



DWV012
or
DWV010
Dust Extractor



DWH9000
AirLock™ Adaptor
Included on DWV012 & DWV010



DWE46152
5" Surface Grinding Dust Shroud



DWV012
or
DWV010
Dust Extractor



DWH9000
AirLock™ Adaptor
Included on DWV012 & DWV010

Copyright ©2017 DeWALT. The following are examples of trademarks for one or more DeWALT power tools and accessories: the yellow and black color scheme, the "D"-shaped air intake grill, the array of pyramids on the handgrip, the kit box configuration, and the array of lozenge-shaped humps on the surface of the tool.

1. System is compliant to the Exposure Control Methods described in Table 1 of 29 CFR 1926.1153 when outlined components are operated and maintained in accordance to manufacturer's instructions, assuming that airflow is measured in accordance with the motor/fan system test. See 'Appendix' for full system and compliance details. OSHA is reviewing the exact requirements for dust extraction in these applications.

* Also fits previous DeWALT models D28402, D28402N, D28110, D28112, D28114, D28114N, D28144, D28144N, D28131, D28140, D28115, D28115N, D28116, D28065, D28065N, D28066N